



PRODUCT SPECIFICATIONS #Z132

CORK RUBBER FLOORING

Available Surface Profiles: Smooth, Hammered, Round Stud, Square Stud

Tile Dimension: 24" X 24" nominal (602mm X 602mm)

Thickness: Smooth and Hammered = 0.10" (2.5mm); Round and Square Stud = 0.12" (3.0mm)

Packaging:

Tiles Per Carton	20
Coverage Per Carton	78 ft ² (7.25 m ²)
Weight Per Carton	64lbs (29 kg)
Carton Dimension	24.2" X 24.2" X 2.5" (615mm X 615mm X 64mm)
Carton Volume	0.85 ft ³ (0.024 m ³)
Adhesive #10	50lbs/4 gal pail – approximate coverage 600ft ² per gallon

Tile Area: 3.9 ft² (.36 m² per tile)

Test Data:

Test Description	Standard	Result	Meets or Exceeds Standard
Smoke Density	ASTM E662	<340	Y
Fire Resistance	ASTM E648	Class I	Y
Fire Resistance	DIN 51960	Class I	
Hardness	Shore A	>85	N/A
Rubber Flooring Standard	ASTM F1344		Y
Tensile Strength		> 46 Kg/cm ²	N/A
Elongation		>110%	N/A
Compression Set	BS 1711-1975	9.5	
Static Load Limit	ASTM F970-00	.0005" @650 lbs after 24 hrs	
Resistance to Cigarette Burns	DIN 51961-1984	No change in color or surface	
Electrical Resistance	BS2050-1978	4.4*10 ⁷ Ohms @ 500 VDC	
Coefficient of Friction	ASTM D2047	.71 Wet; .76 Dry	Y - Meets ADA Recommendations
Chemical Resistance	ASTM F925	Excellent Resistance - Details available upon request	
Mold Resistance	ASTM G-21	Does Not Promote Mold Growth	
CHPS	CA DHS Section 01350 protocol		Yes